

# envioblinds®

LOW CARBON TECHNOLOGY

## HAROL®



## Super-insulating Extra comfort at home

### OB600 - OB700 built-on shutters

With their excellent airtightness and thermal insulation properties, the OB600 and OB700 built-on shutters for newbuilds and renovations easily meet the most stringent energy standards. The acoustic insulation reduces disturbance from street noise and the integrated flyscreen keeps insects out. Of course, the roller shutters also improve security and darken the room if needed. Moreover, the OB700 can be completely concealed within the building.



**MEETS THE MOST  
STRINGENT  
ENERGY STANDARDS**

### Unique properties: OB600 - OB700 built-on shutters

Inspection cover underneath allows the OB700 to be aesthetically concealed within the building

Acoustic insulation (up to 39 dB) reduces disturbance from street noise

Clip technology for quick and easy installation on all window types (PVC, aluminium, wood)

Thermo-slats available for the greatest energy-saving solution



Box lined with Neopor for optimum thermal protection ( $U \geq 0.62 \text{ W/m}^2\text{K}$ )

Durable padding to protect against scratches

Choose from a range of slat types and colours depending on the area of your window and your taste

Integrated flyscreen keeps out mosquitoes and other insects.

OB700 with flyscreen

## A roller shutter for every building project

### OB600

- » Inspection cover at the front
- » Rounded box cover



Available sizes:  
165x175  
205x215

### OB700

- » Inspection cover underneath
- » Can be completely concealed within the building



### OB700

- » Inspection cover at the front
- » Ideal for sliding windows




Available sizes:  
205 x 255  
245 x 255


## The perfect guide rail for every situation

### Standard guide rails

Pvc




Alu




### Distance guide rails

Pvc




Alu




### Flyscreen guide rails

Pvc




Alu



## Greater comfort at home in every season

Pleasant climate indoors in the summer

Insulating in the winter



## Slats for additional security and insulation

Type



	PVC37	PVC MIDI	ALU35	ALU37	ALU42	ALU42S	ALU42TH
Maximum surface area	3 m <sup>2</sup>	5 m <sup>2</sup>	6 m <sup>2</sup>	8 m <sup>2</sup>	10 m <sup>2</sup>	11 m <sup>2</sup>	7 m <sup>2</sup>
Slat thickness	7,8 mm	9 mm	8,85 mm	8,5 mm	9 mm	9 mm	8,5 mm
R-value	0,19 m <sup>2</sup> K/W	0,21 m <sup>2</sup> K/W	0,14 m <sup>2</sup> K/W	0,15 m <sup>2</sup> K/W	0,16 m <sup>2</sup> K/W	0,16 m <sup>2</sup> K/W	0,25 m <sup>2</sup> K/W

## Operating methods

- » Standard wireless two-way control (io)
- » Silensio wireless two-way control (io)
- » Wireless one-way control (RTS)
- » Cabled control
- » Manual control



## Maximum dimensions

- » Max. width: 4.2 m
- » Max. height: 3 m
- » Max. area: 11 m<sup>2</sup>